



**Indian Cardamom Research Institute**

**Spices Board**  
Ministry of Commerce & Industry Govt. of India  
**Myladumpara**  
**Kailasanadu (P.O)**  
**Idukki District 685553**  
**Kerala**

No.ICRI/EDP/HW/2/2007

20<sup>TH</sup> June,2007

Sub: Inviting sealed quotations for purchase of Data Integrater – reg.

Sealed quotations are invited for the supply and installation of a Data Integrater with the configuration given in the annexure. The Sealed Quotation superscribing ‘ Quotation for supply of the Data Integrater – (Computer & Statistics centre)-5.7.2007’ should reach at the following address on or before 5<sup>th</sup> July,2007.

The Director(Research)  
Indian Cardamom Research Institute,  
Spices Board,  
Kailasanadu P O  
Myladumpara – 685 553  
Idukki District.

Sd/-  
DEPUTY DIRECTOR(RESEARCH)

ANNEXURE

Configuration of the Data Integrater :

Processor	Intel Pentium D Processor 945 3 Ghz or above, 2 x 2 MB L2 Cache, 800 MHZ FSB
Chipset	Intel Q963/ICH8 chipset
Memory	1 GB or higher RAM – type DDR2-SDRAM Expandable to 4GB through industry standard DIMM slots
Hard Disk	80GBHDD or higher SATA 7200 RPM 8MB cache NTFS
HD Controller	Serial ATA 3.0 Gb/s
Display	17” TFT monitor set to screen resolution of 1920 x 1200 or 1600 x 1200 or 1280 x 1024
Wireless	Intel PRO/Wireless 3945 LAN
Video Graphics	<b><u>Graphic card minimum values</u></b> 128 MB RAM minimum 128 bit memory bus width 32 bits operation Support Direct X Version 9c Direct X version 10 for Windows Vista PCI Express if installed Recommended minimum graphics adaptors are the Radeon X600 or X800 series Graphics adaptors using the PCI Express bus or later models
I/O Ports	Rear 6USB 2.0, 1 serial port , 1 parallel port, 2 PS/2 , 1 RJ-45, 1VGA audio in/out, MIC in, Front 2 USB 2.0, headphone and microphone
Optical Disk Drive	DVDRW with latest speed
LAN	10/100/1000 MBPS
FDD	1.44 FDD
Key Board	HP PS/2 Standard Keyboard
Pointing Device	2-button Optical Scroll Mouse (USB)
Operating System	Windows XP Professional preloaded
Antivirus	Latest McAfee Antivirus preloaded
Optional	19” color TFT monitor set to screen resolution of 1920 x 1200 or 1600 x 1200 or 1280 x 1024